


# EXZENTER TECHNICAL DATA



		3.0 x 3.0 m	2.0 x 4.0 m	3.0 x 4.0 m
<b>X</b>	Distance from centre pole to outer edge of canopy	100	70	100
	Segments	8	5	8
	Area	9	8	12
<b>A</b>	Height closed incl. top plate	391	370	410
<b>B</b>	Height opened incl. top plate	305	293	300
<b>C</b>	Headroom with valance	215	215	215
<b>D</b>	Headroom without valance	237	237	237
<b>E</b>	Height of valance	28	28	28
<b>F</b>	Ground clearance from spoke edge	144	140	118
<b>G</b>	Height of lower disc flange	250	246	263
	Weight without packaging MayTex-Acrylic without valance	37	27	36
	Support pole diameter	outer-Ø 76, pole thickness 3		
	Packaging cardboard sleeve length 999 cm	Ø 33 cm approx. 17 kg		
	Installation base length/width/min. depth	50/50/60		
	Minimum ballast Number of layers of concrete slabs (250) required	2 x = approx. 224 kg		

<b>X</b>	Distance from centre pole to outer edge of canopy	cm
	Segments	
	Area	m <sup>2</sup>
<b>A</b>	Height closed incl. top plate	cm
<b>B</b>	Height opened incl. top plate	cm
<b>C</b>	Headroom with valance	cm
<b>D</b>	Headroom without valance	cm
<b>E</b>	Height of valance	cm
<b>F</b>	Ground clearance from spoke edge	cm
<b>G</b>	Height of lower disc flange	cm
	Weight without packaging MayTex-Acrylic without valance	kg
	Support pole diameter	mm
	Packaging cardboard sleeve length 999 cm	
	Installation base length/width/min. depth	cm
	Minimum ballast Number of layers of concrete slabs (250) required	

The heights specified are for parasols with MayTex-Acrylic covering fabric that are mounted in an anchor tube SZ150. The increase in height for eccentric parasols with other installation bases can be seen in the list below:

Full frame pedestal: SZ203 + 17 cm  
 Full frame pedestal: SZ412 + 12 cm  
 Anchor plate: SZ131 + 1,5 cm  
 Base plate: SZ273 + 4 cm  
 Base plate: SZ275 + 4 cm

Dimensional tolerance approx. ± 5%



Alignment possibility + special clamp  
 It is only possible to use such installation bases for SCHATTELLO parasols that have a locking hinge or a full-frame pedestal, adjustable for slanting surfaces.  
 Anchoring bases with locking hinge are installed with set screws and a special surface clamp. This ensures that the eccentric parasol will be aligned and mounted completely upright.

